



The Impact of the Energy Management and Monitoring System

¹ Aliyu Hassan Muhammad, ² Ibrahim Umar Tofa, ³ Abdu Isah, ⁴ Abubakar Sani Muhammad, ⁵ Adamu Bello, ^{*6} Muhammad Ahmad Baballe

¹Department of Physics, Bayero University Kano, Kano, Nigeria

²Department of Building Technology, School of Environmental Studies Gwarzo, Kano State Polytechnic, Kano, Nigeria

^{3,4,5}Department of Electrical and Electronic Engineering Technology, School of Technology, Kano State Polytechnic, Kano, Nigeria

⁶Department of Computer Engineering Technology, School of Technology, Kano State Polytechnic, Kano, Nigeria

DOI: [10.5281/zenodo.7059951](https://doi.org/10.5281/zenodo.7059951)

Submission Date: 21st June 2022 | Published Date: 30th Aug. 2022

*Corresponding author: Muhammad Ahmad Baballe

Department of Computer Engineering Technology, School of Technology, Kano State Polytechnic, Kano, Nigeria

ORCID: 0000-0001-9441-7023

Abstract

Nowadays, efficient energy utilization is the utmost priority in many industries so as to minimize the energy cost. The power management and monitoring system is actually an energy efficient technique that usually helps the power managers by providing comments on different operating practices and the inferences of the power management systems. They also mentor on the level of energy usage that is expected in a particular period of time. These management systems also provide information in advance regarding excess energy consumption due to malfunctioning of equipment and lack of effective maintenance. The aim of power management systems is to support business managers in identifying surplus usage of energy, predicting the trend in energy consumption by visualizing it, and calculating the usage of power in the future. An autonomous energy monitoring system is a part of energy management, which is an endless process.

Keywords: Programmable Logic Controller, Energy Management System, Power Consumption Information, Remote Terminal Unit, Multifunction Meter

INTRODUCTION

Power management and monitoring systems are actually energy-efficient methods that usually aid the power managers by providing comments on different operating practices and the inferences of the power management systems. They likewise mentor on the level of energy usage that is expected in a particular period of time. These management systems likewise provide information in advance regarding excess energy consumption due to malfunctioning of equipment and lack of effective maintenance. The purpose of power management systems is to support business managers in detecting surplus usage of energy, predicting the inclination in consumption of energy by envisioning it and calculating the usage of power in the future. An independent energy monitoring system is a part of energy management, which is an endless process. As a first step, the area, for example, plant area, office building, process steps, etc., for which energy conservation measures are required should be identified and a basic model must be built for that area. Process steps can also be considered as a field for energy conservation measures to professionally use energy. As a next step, the energy in the existing situation is measured and monitored, which will result in the creation of a basic archetypal. The basic prototypical can be constructed either with the aid of historical information about energy that is consumed or from the standard information given by the manufacturers. After creating the basic archetypal, we can implement the program of energy conservation measures. By this way, we can improve the effectiveness of the power utilization of the system and likewise replace devices that consume high energy. Once this energy conservation measure program is implemented, then from the results of the program, we can actually compare between the basic prototypical and actual energy usage [1].

Related Works

This research aims to deliver the methods involved in the control of load in industry during heavy traffic with the aid of programmable logic controllers (PLC). It likewise clarifies the use of monitoring all the load parameters of the motor on a personal computer (PC). In the considered paper, we have implemented the multifunction meter (MFM) to PLC communication with Modbus Remote Terminal Unit (RTU) communication; direct values from the MFM are taken as feedback to the PLC. Firstly, constant current values for a single load are taken into consideration, and if any higher load is being applied to the current load, the difference in amps rating is taken as reference and the extra load gets tripped at the same time power is managed. With the aid of energy meters, voltage and ampere ratings are constantly observed. If differences in loads are observed rather than any pre-defined load, alarms occur in Supervisory Control and Data Acquisition (SCADA) and power and energy are managed [1]. In this research, we discuss how we remotely monitor and control the home power management system through the cloud using any Internet-enabled device as a remote controller, even when we are not in the vicinity of the house [2]. In this paper, by applying MQTT, an Internet of Things (IoT) standard protocol, to the Zigbee network environment, MQTT performs the role without adding a separate gateway and automatically controls power and standby power through weight-based usage pattern analysis. As a result of comparing and evaluating the implemented system with previous studies, it was confirmed that the average power consumption was reduced by about 3.25% and the average standby power consumption by 13.06% [3]. In this paper, an algorithm for removing the features of home appliances and automatically building a database to identify home appliances is designed and presented. For the verification, a software library supporting this algorithm has been implemented and added to a power management system server, which has already been executed to support real-time monitoring of home appliances' power consumption status and control their power. The executed system consists of a system server and clients, each of which measures the power consumed by a home appliance plugged into it and transmits the information to the server in real-time over a wireless network. Through experiments, it is verified that it is possible to identify any home appliance connected to a specific client [4]. This paper describes a system that combines mechanisms for home appliance protection and management. The proposed system is centrally managed by a microcontroller with a liquid crystal display (LCD) interface and a push button for user management. Voltage limits and power consumption by loads are regulated by the system, making it very suitable for home use. The software module driving the microcontroller was implemented using the C programming language. The power management system allows users to create ON/OFF schedules and other user-defined requirements [5]. This study presents the feasibility study of home appliances to be applied for appliance to grid mode of operation. The analysis includes topology and control modifications to support the concept of a supportive platform provided by smart homes and smart grid. Home appliances are then proposed as new distributed reactive sources, which are utilized to resolve the issue of voltage regulation as well as produce reactive power locally for voltage stability. This study discusses the technical transitions in current home appliances to accommodate auxiliary functionality of grid reactive power support (RPS) and how it can fit into the home energy management system architecture to provide the required RPS [6]. In this research, we primarily focus on the design and implementation of a GSM-based household power management system to remotely control at most ten home appliances through a mobile phone connected to an automated device's microcontroller using wireless technology. This developed system allows the user to start or stop appliances from afar and sends back a message to familiarize the user with the status (ON/OFF) of all the devices under consideration. Thus, from the design and implementation of the GSM based household power management system, users can control their household appliances outside their abodes using mobile phones, manage their power consumption and prevent unauthorized individuals from controlling their appliances [7].

Components Used In the Implementation of the Power Management and Monitoring System

1. **Programmable Logic Controller:** The most frequently used digital computer in industrial mechanical processes for automation is the Programmable Logic Controller (PLC). The PLC finds its applications in processes like the controlling of machines on assembly lines, amusement rides, etc. The key purpose of the design of PLC is to be used in many industries and machines for both analog and digital inputs and outputs. The features of the PLC are that it can be operated in extreme temperature ranges and is not affected by any electrical noises.
2. **Multifunction Energy Meters:** They are used for monitoring electrical installations. The Multifunction energy meter is used to monitor and measure all the electrical parameters such as active power, voltage, apparent power, current, power factor, reactive power, active energy, phase angle and so on.



Fig. 1: Multifunction Energy Meter

3. The remote terminal unit (RTU): This is a microprocessor-based electronic device used in industrial control systems (ICS) to connect various hardware to distributed control systems (DCS) or supervisory control and data acquisition (SCADA). The RTUs pass sensor information from input streams in control loops to an output stream to be forwarded on to centralized control in an ICS. The RTUs automatically negotiate connections to either local or remote controls. The RTUs monitor both digital and analog field information. The RTU gets the information from sensors monitoring target industrial process variables and then forwards that information onto centralized monitoring and control. The hardware of the RTU contains the setup software required to connect information output streams, communication protocols, and built-in troubleshooting. The devices are often powered by alternative current (AC) mains with direct current (DC) converters and sometimes battery backup.



4. The supervisory control and data acquisition (SCADA): SCADA Systems are vital for industrial organizations since they help to maintain efficiency, process information for smarter decisions, and communicate system issues to help mitigate downtime. The basic SCADA architecture begins with programmable logic controllers (PLCs) or remote

terminal units (RTUs). The PLCs and RTUs are microcomputers that communicate with an array of objects such as factory HMLs, machines, sensors, and end devices, and then route the data from those objects to computers with SCADA software. The SCADA software processes, distributes, and displays the information, helping operators and other employees analyze the information and make significant decisions. For instance, the SCADA system quickly informs an operator that a batch of products is showing a high incidence of errors. The operator pauses the operation and views the SCADA system information through an HMI to determine the cause of the issue. The operator reviews the information and discovers that Machine 4 was malfunctioning. The SCADA system's ability to inform the operator of an issue aids him to resolve it and prevent further loss of product.



Fig. 3: Supervisory Control and Data Acquisition (SCADA)

IMPACTS OF THE ENERGY MANAGEMENT SYSTEM

1. **Cost Reduction:** The major reimbursements of implementing a facilities management system are the reduction in operational costs such as cooling, heating, lighting, and water services. The energy management aids incessantly tracking your energy usage over a period of time and storing this information so you can have constant access to your building's historical energy performance, allowing you to make calculated cost predictions on future usage. As many businesses across industries have struggled to adapt to the cost implications caused by the COVID-19 pandemic, one way to reduce your current operational costs is through energy management, with studies showing businesses can save up to almost 39.8% on average costs over a twelve-month period.
2. **Lowered Carbon Footprint:** The carbon footprint of your property is the total amount of greenhouse gases generated by our actions and is directly linked to the energy that it consumes. Having a system in place to continuously measure and control this can aid in highlighting deficiencies in your energy system that can be improved upon to lessen your environmental impact. According to the International Energy Agency (IEA), the building and construction industries are responsible for about 29.8% of global energy usage and almost 39.9% of overall carbon emissions. As many governments around the world are considering how to reduce overall emissions, energy-reduction strategies will be more important than ever, with studies showing how smart energy controls such as Energy Management Systems can reduce worldwide buildings' energy consumption by 10% by 2039.
3. **Enhanced Productivity and Wellbeing:** An additional major aspect of energy management (EMS) is the ability to control every aspect of your building's energy performance, such as HVAC and lighting, enabling you to create a comfortable working environment for staff. 60% of the workers are said to be disappointed with the temperature and lighting control within an office environment, which has had negative effects on the overall productivity, with at least 89.9% of the employees affected over a twelve-month period. As mentioned earlier, an energy management system will help reduce your building's carbon footprint through the employment of energy-efficient measures. Globally, as more and more people are becoming more environmentally mindful, improving your building's energy management is a more modern method of improving your employee gratification.
4. **Return-on-Investment:** Energy management systems (EMS) frequently include built-in cost-saving features such as emitting less power during peak periods, offering revenue-generating programs, and detecting potential energy leaks. alone will help you see an almost immediate return on investment after the initial installation cost of an EMS. It is imperative to highlight that businesses and property owners who implement systems that are customized for their unique building needs to improve ROI as each premise has different requirements. For instance, healthcare buildings

such as hospitals may need increased energy usage over a sustained time period, whereas educational facilities such as schools may want more energy throughout the daytime period and less overnight.

5. Improved Brand Image: Implementing an Energy Management System (EMS) into your business and building can help improve the image of your brand to potential investors and other key stakeholders. Companies around the globe are highlighting what they are doing to make their practices more environmentally friendly, and introducing an Energy Management System (EMS) can be a good place to start. Making this change isn't just for big businesses, as increasing numbers of small and medium-sized companies are starting to recognize the advantages of implementing energy savings procedures. People are now looking to be involved with companies that are doing their part for the planet, which is why these businesses see annual growth of 15% compared to their competitors [8].

CONCLUSION

This review paper proposed a system that observes the energy usage in several divisions of the plants. The actual energy that is consumed is monitored by SCADA and a comparison is made also. By comparison with the regular requirements of energy consumption, the wastage of energy is measured. An alert can be made by the proposed system in case of an emergency. Also, the impact of the energy management system is discussed.

REFERENCES

1. K. Ganesan, N. V. A. Grace, P. A. S. Dhas, "Auto Power Management System", Turkish Journal of Computer and Mathematics Education Vol.12, No.12, pp. 804-809, 2021.
2. Maiti, S. Sivanesan, "Controlling and Monitoring of Home Power Management Systems through Public Cloud Services", pp. 1-6, s publication at: <https://www.researchgate.net/publication/299447247>.
3. Y. Jang, S. Lee, "Design and Implementation of MQTT-based Power Management System through Analysis of Home Appliance Usage Patterns" Journal of Next-generation Convergence Information Services Technology, Vol.9, No.4, pp.363-375, <http://dx.doi.org/10.29056/jncist>, 2020.
4. S. Hong, K. Choi, J. Hong, "Design for Automatic Building of a Device Database and Device Identification Algorithm in Power Management System", Journal of Korean Institute of Intelligent Systems, Vol. 24, No. 4, pp. 403-411 <http://dx.doi.org/10.5391/JKIIIS>, pp. 403-411, August 2014.
5. O. O. Basorun, "Home Appliances Power Management System Journal of Advancement in Engineering and Technology, Journal homepage: <http://scienceq.org/Journals/JAET.php>, Vol. 3, No. 3, pp. 1-3, 15 September 2015.
6. S. Gautam, D. D. Lu, W. Xiao, Y. Lu, "Realisation of RPS from electrical home appliances in a smart home energy management system" IET Smart Grid, e <http://creativecommons.org/licenses/>, Vol. 3, No. 1, pp. 11-21, 2020.
7. M. Young, the Technical Writer's Handbook. Mill Valley, CA: University Science, 1989.
8. <https://lawlerconsulting.com/5-benefits-of-an-energy-management-system/>

CITE AS

Aliyu H. M., Ibrahim U. T., Abdu Isah, A. Sani M., Adamu Bello, & Muhammad A. Baballe. (2022). The Impact of the Energy Management and Monitoring System. Global Journal of Research in Engineering & Computer Sciences, 2(4), 14–18. <https://doi.org/10.5281/zenodo.7059951>